

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
7 April 2005 (07.04.2005)

PCT

(10) International Publication Number
WO 2005/030668 A2

(51) International Patent Classification⁷:

C04B

(21) International Application Number:

PCT/US2004/031703

(22) International Filing Date:

27 September 2004 (27.09.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/506,387 26 September 2003 (26.09.2003) US

(71) Applicant (for all designated States except US): EISENMANN CORPORATION [US/US]; 150 E. Dartmoor Drive, Crystal Lake, IL 60014 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): WOODSIDE, J., Russell [US/US]; 1564 Magnolia Drive, Crystal Lake, IL 60014 (US). WASHBURN, Ryan, F. [US/US]; 961 North Shore Drive, Crystal Lake, IL 60014 (US).


(74) Agents: FRANCISSEN, Vernon, W. et al.; Gardner Carlton & Douglas LLP, Suite 3700, 191 North Wacker Drive, Chicago, IL 60606-1698 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR FIRING BRICKS



(57) Abstract: A method for firing bricks provides a kiln car including furniture with silicon carbide vertical supports. In one embodiment, horizontal support beams are mounted to the vertical supports to define multiple vertical levels and support crossbeams. Low sets of bricks are positioned on a first carriage having a conveyor, near one side of the kiln car. A second carriage is extended beneath crossbeams for one level to a position adjacent the first carriage. The second carriage includes spaced-apart rollers that interfit between crossbeams for the level when the carriages are raised, so that tops of the rollers are slightly above the crossbeams. The rollers convey bricks to a desired position, and the carriages are lowered to rest the bricks on the crossbeams. Another embodiment uses a fork to load and unload crossbeams carrying bricks from the horizontal support beams.

WO 2005/030668 A2



Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.